


Tube No.
130U

ISOPROPYL MERCAPTAN



1. PERFORMANCE


- 1) Measuring range : 1-10 ppm 0.5-5 ppm
Number of pump strokes : 1/2 (50mL) 1(100mL)
- 2) Sampling time : 1 minute/1 pump stroke
- 3) Detectable limit : 0.2 ppm(100mL)
- 4) Shelf life : 2 years
- 5) Operating temperature : 0~40°C
- 6) Reading : Direct reading from the scale calibrated by Methyl mercaptan at 1 pump stroke
- 7) Colour change : Pale yellow → Pink

2. RELATIVE STANDARD DEVIATION

RSD-low : 10% RSD-mid. : 5% RSD-high : 5%

3. CHEMICAL REACTION

By reacting with Mercuric chloride, Hydrogen chloride is produced and PH indicator is discoloured.



4. CALIBRATION OF THE TUBE

PERMEATION TUBE METHOD

5. INTERFERENCE AND CROSS SENSITIVITY

| Substance | Interference | Coexistence |
|-------------------|----------------------------------|---|
| Arsine | Similar stain is produced. | Higher readings are given. |
| Hydrogen selenide | " | " |
| Phosphine | " | " |
| Hydrogen sulphide | " | " |
| Hydrogen cyanide | Whole reagent is changed to Red. | " |
| Sulphur dioxide | | Whole reagent is changed to Pale red, but Pink stain indicates Mercaptans conc. |

(NOTE)

In case of 1/2 pump strokes, following formula is available for the actual concentration.

Actual concentration = 2 × Reading value

This tube scale is calibrated based on Methyl mercaptan and the same scale is available for Isopropyl mercaptan.